

Flexigas

The fast and truly versatile
system for **gas installations**



bsi.
Stainless Steel Corrugated
Semi-rigid Tubing
KITEMARK™

KM 598726
EN 15266



Flexigas

Always innovating

Flexigas™, designed for domestic and commercial gas installations is the intelligent choice for plumbers who are looking for an efficient, lightweight and flexible alternative to rigid copper or steel. Through constant innovation, Flexigas™ continues to develop faster, easier and safer solutions for gas installations. Flexigas™ hold a number a patented and patent pending features, including Flexigas DS™, FG Link™, FG Bond™, and FG Wrap™.

Flexigas™ is approved by British Standards under the KiteMark certification scheme and is manufactured in accordance with EN 15266.



KM 598726
EN 15266



Gas.BE
EN 15266

The most **flexible** CSST system in the UK






Made from a sheet of stainless steel formed into a series of corrugations, Flexigas™ tubing bends easily by hand while still maintaining the integrity and strength of a steel tube



Flexible Steel Tubing.

The corrugations in the tubing allow for flexibility without sacrificing on strength, compressing together on the inside edge and slightly expanding on the outside edge to easily create any angle required.



Flexible Steel Tubing has been around for some time. It was originally developed in Japan in the 1980's as it is a far safer option in earthquake prone environments allowing the gas installation some flexibility during a seismic event. Due to numerous additional safety features and the fact that installation times can be significantly reduced, corrugated stainless steel tubing systems have since become widespread throughout North America, and more recently in Europe.

**Easier, faster and safer:
offering a solution for every
installation**





As Flexigas™ can be bent by hand and passed through interior spaces easily, it can be installed quickly using long continuous runs of tubing, making installs up to 4x faster than copper or rigid steel.

The patented Flexigas™ fittings ensure a secure seal in a matter of seconds without the need for any specialist tools. No soldering, sealants or heavy crimping tools are required.

In addition, as Flexigas™ requires far fewer fittings than traditional methods there are far fewer locations where a gas leak might occur.

**Every installation
scenario covered.**

Introducing Flexigas DS™

- ✓ Solid floors
- ✓ Solid walls and structural elements of a building
- ✓ Earth or ground / soil
- ✓ Screed
- ✓ Unventilated voids
- ✓ Unventilated risers - small annulus means suitable for direct clipping

Flexigas - DN22

10018 Super

Flexigas DS™ is a patent pending, double layered flexible gas piping system consisting of a:


- 1st inner CSST layer (Corrugated Stainless Steel Tubing) plus a yellow polyethylene cover.
- 2nd outer sleeve layer, including V0 fire rated corrugated sleeving, with an exterior polyethylene cover.

The outer sleeve layer is designed specifically to meet the definition of a sleeve according to UK regulations (BS 6891 and ISEM/UP/2, 3 & 7), and is in slidable configuration with the inner CSST layer.

Flexigas DS™ consists of a very small annulus between the layers, keeping the overall diameter to a minimum, while still allowing the inner CSST to be inserted and withdrawn if necessary.

Flexigas DS™ can be used to pass through 100% of all installation scenarios, straight out of the box, without adding additional sleeving on site.





Sleeve layer

Small annulus

CSST layer

Flexi

Flexi



Flexigas

DN2

1001M

Flexigas

008M

Flexigas

Flexigas

Flexigas

DS

bar

DS - DN2

Flexigas DS™ FAQ

What is the definition of a sleeve in UK regulations?

In BS 6891 (Section 3.38) - a protective pipe forming an annulus embedded in the structure through which pipework can be inserted and withdrawn.

In IGEM/UP/2 (Section 5.2.7) - a sleeve is defined as a case (normally tubular) inserted through a void or space in a building for the reception of a gas installation pipe and is impermeable to gas (known as pipe in pipe). Where pipework is required to be enclosed in a sleeve, for example when passing through a wall or unventilated void, the factory applied coating on copper pipe or pliable corrugated stainless-steel tube shall not be considered to fulfil such a purpose.

Is it a requirement to use a pre-sleeved product like Flexigas DS?

No, standard Flexigas™ can of course be used for all gas installations. However depending on the installation, sleeving may be required to pass through certain sections of the installation, for example, through a solid wall or an unvented area.

What is the advantage of using Flexigas DS™?

The advantage is that Flexigas DS™ can be used to pass through 100% of all installation scenarios, straight out of the box, without adding additional sleeving on site. Flexigas DS™ will save a lot of time on complicated installations, where sleeving is required.

Where can Flexigas DS™ be used as a sleeve?

Everywhere (subject to BS 6891 and IGEM regulations), including:

- Solid floors
- Solid walls and structural elements of a building
- Earth or ground / soil
- Screed
- Unventilated voids
- Unventilated risers - small annulus means suitable for direct clipping

**An endless possibility
of connections with
FGLink™, the UK's
largest range of CSST
fittings**





We have partnered with FlowFlex, the UK's largest brass fittings manufacturer, to develop over 150+ fittings. Our huge range of fittings includes more than 55 copper connection fittings and 25+ DN40 fitting types.


The Flexigas™ and FGLink™ patented, and patent pending fittings makes Flexigas™ truly the most versatile gas system on the market. The one-step connection between copper and Flexigas™ leads to endless possibilities, giving you the best of both worlds.



FG Bond™ - The first integrated earthing terminal for CSST



With gas plumbing, safety is a priority. All gas lines must be electrically bonded. Using our patent pending integrated bonding terminal, with Flexigas fittings, makes bonding simple and easy - eliminating the need for clamps or awkward and time-consuming bonding methods.



The FG Bond TM integrated bonding terminal is included
in our Kitemark from BSI, and has been certified as
meeting the relevant tests from BS 951:2009
BS 951 and BS 7671 compliant tag included



KM 598726
EN 15266
BS 951:2009



FG

FIEN



Secure metal-metal seal in seconds

Our patented sealing method creates a 100% metal-metal seal in seconds. As the fitting is tightened, the last corrugation of Flexigas™ tubing is deformed into a flared configuration against the metal seat of the fitting. The sizable and reversible collars are easy to handle and align the Flexigas™ tubing with the fitting during installation.

Integrated tail for a neater finish

All Flexigas™ fittings include an integrated tail, providing a neater surface on which silicone tape can be applied.

All Flexigas™ boxes and spools include 1 x roll of free silicone tape.





On-demand tubing

The Flexigas™ spool roller allows 300-400m coils to be easily unrolled on site, allowing for exact measurements and cuts with no wastage. Alternatively, Flexigas™ is also available in custom lengths for project work.

Installation Guide

The Flexigas™ system has been designed with safety, simplicity and ease of use as the key components. The following seven steps will guide you how to attach a Flexigas™ fitting to tube, create a 100% metal seal and finish off the installation with everything being electrically bonded.

Step 1 Cut

Using a wheel metal pipe cutter, ensure the cut is centred in the valley between corrugations and the cutter is only slightly tightened on each full revolution around the tube. Make sure the cut is clean and circular with no sharp edges.



Step 2 Remove

With a utility knife, safely remove the flame retardant yellow cover so that the last four corrugations are exposed.



Step 3 Slide

Slide the nut over the tubing and then place the two semi-circular collars around the tubing so that the ridges on the collars occupy the last three valleys of the tubing.



Step 4 Tighten

Tighten the nut and fitting using two suitably sized wrenches. The seal is formed when the last corrugation deforms around the seat inside the fitting. Use sufficient torque.



Step 5 Wrap

After conducting a gas tightness test, wrap the small gap between the "tail" on the nut and tube using yellow silicone tape.



Step 6 Attach

Place the warning notice between earthing terminal and the nut, and then attach the earthing terminal to the nut.



Step 7 Bond

Strip earthing cable to reveal 1-2cm of copper wire. Screw down onto copper wire.





What certifications does Flexigas™ have?

Flexigas™ is certified under the British Standards KiteMark certification scheme. The Kitemark is recognised throughout the UK and the world as a mark of a truly quality product. Not only have we tested Flexigas directly with British Standards but as part of the Kitemark scheme our products undergo regular on-going testing and manufacturing locations are audited regularly by British Standards.

Flexigas™ is manufactured in accordance with EN 15266. Additionally Flexigas™ has GAS.BE certification in Belgium.



KM 598726
EN 15266



Gas.BE
EN 15266



Flexigas

— DN28 (UK) /

DN25 (EU) —

As part of the BSI Kitemark certification scheme Flexigas™ has undergone testing under fire conditions and has passed both EN1775 Annex A & B, and can therefore be used in protected areas.

Key Features

British Standards KiteMark Certified.

UK's largest CSST fitting range with over 130 fittings, and 25+ DN40 fittings.

Wide range of unique and innovative patented solutions.

Easy integration with copper installations.

Designed for all domestic and commercial gas projects.

Integrated FG Bond™ earthing terminal to make earth bonding easy.

Can be buried in screed or the ground without additional protection.

Unique tail on fitting means that only a small gap must be silicone taped resulting in a neater finish.

Free silicone tape included with every box and spool.

Metre marking (up to 400m) for easier installation.

No specialist tools required.

Specifically designed for UK market - uses 22mm and 28mm tube diameters.

Custom lengths for project work available. Tube lengths cut in the UK to order.



Flexigas™ Products

FLEXIGAS CSST



Description	Code
DN15 Pipe - 15 Metres	DN15-15
DN15 Pipe - 25 Metres	DN15-25
DN15 Pipe - 50 Metres	DN15-50
DN15 Pipe - 75 Metres	DN15-75
DN22 Pipe - 15 Metres	DN22-15
DN22 Pipe - 25 Metres	DN22-25
DN22 Pipe - 50 Metres	DN22-50
DN22 Pipe - 75 Metres	DN22-75
DN22 Pipe - 100 Metres	DN22-100
DN22 Pipe - 400 Metres	DN22-400
DN28 Pipe - 15 Metres	DN28-15
DN28 Pipe - 25 Metres	DN28-25
DN28 Pipe - 50 Metres	DN28-50
DN28 Pipe - 75 Metres	DN28-75
DN28 Pipe - 100 Metres	DN28-100
DN28 Pipe - 400 Metres	DN28-400
DN32 Pipe - 15 Metres	DN32-15
DN32 Pipe - 25 Metres	DN32-25
DN32 Pipe - 50 Metres	DN32-50
DN32 Pipe - 75 Metres	DN32-75
DN32 Pipe - 90 Metres	DN32-90
DN32 Pipe - 100 Metres	DN32-100
DN32 Pipe - 350 Metres	DN32-350
DN40 Pipe - 15 Metres	DN40-15
DN40 Pipe - 25 Metres	DN40-25
DN40 Pipe - 50 Metres	DN40-50
DN40 Pipe - 75 Metres	DN40-75
DN40 Pipe - 100 Metres	DN40-100
DN40 Pipe - 200 Metres	DN40-200
DN50 Pipe - 15 Metres	DN50-15
DN50 Pipe - 25 Metres	DN50-25
DN50 Pipe - 50 Metres	DN50-50
DN50 Pipe - 75 Metres	DN50-75
DN50 Pipe - 100 Metres	DN50-100
DN50 Pipe - 150 Metres	DN50-150

FLEXIGAS DS



Description	Code
DN15 Double Sleeved - 25m	DS-15-25
DN15 Double Sleeved - 50m	DS-15-50
DN15 Double Sleeved - 75m	DS-15-75
DN22 Double Sleeved - 15m	DS-22-15
DN22 Double Sleeved - 25m	DS-22-25
DN22 Double Sleeved - 50m	DS-22-50
DN22 Double Sleeved - 75m	DS-22-75
DN22 Double Sleeved - 100m	DS-22-100
DN28 Double Sleeved - 25m	DS-28-25
DN28 Double Sleeved - 50m	DS-28-50
DN28 Double Sleeved - 75m	DS-28-75
DN28 Double Sleeved - 100m	DS-28-100
DN32 Double Sleeved - 25m	DS-32-25
DN32 Double Sleeved - 50m	DS-32-50
DN32 Double Sleeved - 75m	DS-32-75
DN32 Double Sleeved - 100m	DS-32-100
DN40 Double Sleeved - 25m	DS-40-25
DN40 Double Sleeved - 50m	DS-40-50
DN40 Double Sleeved - 75m	DS-40-75
DN40 Double Sleeved - 100m	DS-40-100
DN50 Double Sleeved - 25m	DS-50-25
DN50 Double Sleeved - 50m	DS-50-50
DN50 Double Sleeved - 75m	DS-50-75
DN50 Double Sleeved - 100m	DS-50-100

ON-SITE SPOOL ROLLING KIT - CODE SPL-01

Allows for the unrolling of 400m /350m lengths.
Eliminates wastage on site.



Flexigas™ Products

Flexigas™ Standard Contractor Kits - include a 5, 10 or 15m length of standard Flexigas tube, either 2 x Male or 2 x Copper Connectors, and 1 roll of silicone tape.

STD CONTRACTOR KITS - CC



Description	Code
DN15 - 5m w/ 2x Copper Unions	CK15-5m-CC
DN15 - 10m w/ 2x Copper Unions	CK15-10m-CC
DN15 - 15m w/ 2x Copper Unions	CK15-15m-CC
DN22 - 5m w/ 2x Copper Unions	CK22-5m-CC
DN22 - 10m w/ 2x Copper Unions	CK22-10m-CC
DN22 - 15m w/ 2x Copper Unions	CK22-15m-CC
DN28 - 5m w/ 2x Copper Unions	CK28-5m-CC
DN28 - 10m w/ 2x Copper Unions	CK28-10m-CC
DN28 - 15m w/ 2x Copper Unions	CK28-15m-CC
DN32 - 5m w/ 2x Copper Unions	CK32-5m-CC
DN32 - 10m w/ 2x Copper Unions	CK32-10m-CC
DN32 - 15m w/ 2x Copper Unions	CK32-15m-CC
DN40 - 5m w/ 2x Copper Unions	CK40-5m-CC
DN40 - 10m w/ 2x Copper Unions	CK40-10m-CC
DN40 - 15m w/ 2x Copper Unions	CK40-15m-CC

STD CONTRACTOR KITS - MALE



Description	Code
DN15 - 5m w/ 2x Male fittings	CK15-5m-Male
DN15 - 10m w/ 2x Male fittings	CK15-10m-Male
DN15 - 15m w/ 2x Male fittings	CK15-15m-Male
DN22 - 5m w/ 2x Male fittings	CK22-5m-Male
DN22 - 10m w/ 2x Male fittings	CK22-10m-Male
DN22 - 15m w/ 2x Male fittings	CK22-15m-Male
DN28 - 5m w/ 2x Male fittings	CK28-5m-Male
DN28 - 10m w/ 2x Male fittings	CK28-10m-Male
DN28 - 15m w/ 2x Male fittings	CK28-15m-Male
DN32 - 5m w/ 2x Male fittings	CK32-5m-Male
DN32 - 10m w/ 2x Male fittings	CK32-10m-Male
DN32 - 15m w/ 2x Male fittings	CK32-15m-Male
DN40 - 5m w/ 2x Male fittings	CK40-5M-Male
DN40 - 10m w/ 2x Male fittings	CK40-10M-Male
DN40 - 15m w/ 2x Male fittings	CK40-15M-Male
DN50 - 5m w/ 2x Male fittings	CK50-5M-Male
DN50 - 10m w/ 2x Male fittings	CK50-10M-Male
DN50 - 15m w/ 2x Male fittings	CK50-15M-Male

Flexigas DS™ Contractor Kits - Flexigas also offer contractor kits in our DS range, which include a 5, 10 or 15m length of Flexigas DS tube, either 2 x Male or 2 x Copper Connectors, and 1 roll of silicone tape.

DS CONTRACTOR KITS - CC



Description

Code

DS-15 - 5m w/ 2x Copper Unions	DS-CK15-5m-CC
DS-15 - 10m w/ 2x Copper Unions	DS-CK15-10m-CC
DS-15 - 15m w/ 2x Copper Unions	DS-CK15-15m-CC
DS-22 - 5m w/ 2x Copper Unions	DS-CK22-5m-CC
DS-22 - 10m w/ 2x Copper Unions	DS-CK22-10m-CC
DS-22 - 15m w/ 2x Copper Unions	DS-CK22-15m-CC
DS-28 - 5m w/ 2x Copper Unions	DS-CK28-5m-CC
DS-28 - 10m w/ 2x Copper Unions	DS-CK28-10m-CC
DS-28 - 15m w/ 2x Copper Unions	DS-CK28-15m-CC
DS-32 - 5m w/ 2x Copper Unions	DS-CK32-5m-CC
DS-32 - 10m w/ 2x Copper Unions	DS-CK32-10m-CC
DS-32 - 15m w/ 2x Copper Unions	DS-CK32-15m-CC

DS CONTRACTOR KITS - MALE



Description

Code

DS-15 - 5m w/ 2x Male fittings	DS-CK15-5m-Male
DS-15 - 10m w/ 2x Male fittings	DS-CK15-10m-Male
DS-15 - 15m w/ 2x Male fittings	DS-CK15-15m-Male
DS-22 - 5m w/ 2x Male fittings	DS-CK22-5m-Male
DS-22 - 10m w/ 2x Male fittings	DS-CK22-10m-Male
DS-22 - 15m w/ 2x Male fittings	DS-CK22-15m-Male
DS-28 - 5m w/ 2x Male fittings	DS-CK28-5m-Male
DS-28 - 10m w/ 2x Male fittings	DS-CK28-10m-Male
DS-28 - 15m w/ 2x Male fittings	DS-CK28-15m-Male
DS-32 - 5m w/ 2x Male fittings	DS-CK32-5m-Male
DS-32 - 10m w/ 2x Male fittings	DS-CK32-10m-Male
DS-32 - 15m w/ 2x Male fittings	DS-CK32-15m-Male

DS CAPS

Optional Caps to complete your Flexigas DS installation for a neater finish

Code

Cap-DS-15	Cap-DS-22
Cap-DS-28	Cap-DS-32
Cap-DS-40	Cap-DS-40



Flexigas™ Products

MALE



Description	Code
DN15 x 1/2" Male BSP	SM 15-12
DN15 x 3/4" Male BSP	SM 15-34
DN22 x 3/4" Male BSP	SM 22-34
DN22 x 1" Male BSP	SM 22-10
DN28 x 1" Male BSP	SM 28-10
DN32 x 1 1/4" Male BSP	SM 32-114
DN40 x 1 1/2" Male BSP	SM 40-12
DN50 x 2" Male BSP	SM 50-20

FEMALE



Description	Code
DN15 x 1/2" Female BSP	SF 15-12
DN15 x 3/4" Female BSP	SF 15-34
DN15 x 1" Female BSP	SF 15-10
DN22 x 1/2" Female BSP	SF 22-12
DN22 x 3/4" Female BSP	SF 22-34
DN22 x 1" Female BSP	SF 22-10
DN28 x 1" Female BSP	SF 28-10
DN28 x 1 1/4" Female BSP	SF 28-114
DN32 x 1 1/4" Female BSP	SF 32-114
DN32 x 1 1/2" Female BSP	SF 32-112
DN40 x 2" Female BSP	SF 40-20

UNIONS



Description	Code
DN15 Straight Union	SU 15
DN22 Straight Union	SU 22
DN28 Straight Union	SU 28
DN32 Straight Union	SU 32
DN40 Straight Union	SU 40
DN50 Straight Union	SU 50

REDUCING UNION



Description	Code
DN22-15 Reducing Union	SR 22-15
DN28-15 Reducing Union	SR 28-15
DN28-22 Reducing Union	SR 28-22
DN32-22 Reducing Union	SR 32-22
DN32-28 Reducing Union	SR 32-28
DN40-22 Reducing Union	SR 40-22
DN40-32 Reducing Union	SR 40-32

COPPER TO FG UNION



Description

Code

DN15 x 15mm Copper Compression	CC 15-15
DN15 x 22mm Copper Compression	CC 15-22
DN15 x 28mm Copper Compression	CC 15-28
DN22 x 15mm Copper Compression	CC 22-15
DN22 x 22mm Copper Compression	CC 22-22
DN22 x 28mm Copper Compression	CC 22-28
DN28 x 22mm Copper Compression	CC 28-22
DN28 x 28mm Copper Compression	CC 28-28
DN28 x 35mm Copper Compression	CC 28-35
DN32 x 22mm Copper Compression	CC 32-22
DN32 x 28mm Copper Compression	CC 32-28
DN32 x 35mm Copper Compression	CC 32-35
DN32 x 42mm Copper Compression	CC 32-42
DN40 x 28mm Copper Compression	CC 40-28
DN40 x 35mm Copper Compression	CC 40-35
DN40 x 42mm Copper Compression	CC 40-42
DN40 x 54mm Copper Compression	CC 40-54

COPPER TO FG ELBOWS



Description

Code

DN15 x 15mm Copper Elbow	ECC 15-15
DN15 x 22mm Copper Elbow	ECC 15-22
DN15 x 28mm Copper Elbow	ECC 15-28
DN22 x 15mm Copper Elbow	ECC 22-15
DN22 x 22mm Copper Elbow	ECC 22-22
DN22 x 28mm Copper Elbow	ECC 22-28
DN28 x 22mm Copper Elbow	ECC 28-22
DN28 x 28mm Copper Elbow	ECC 28-28
DN28 x 35mm Copper Elbow	ECC 28-35
DN32 x 28mm Copper Elbow	ECC 32-28
DN32 x 35mm Copper Elbow	ECC 32-35
DN32 x 42mm Copper Elbow	ECC 32-42
DN40 x 35mm Copper Elbow	ECC 40-35
DN40 x 42mm Copper Elbow	ECC 40-42
DN40 x 54mm Copper Elbow	ECC 40-54

FG BOND™ - CODE EB-01

Patented 1 step earthing terminal



Flexigas™ Products

ELBOWS



Description	Code
Elbow DN15	EE 15
Elbow DN22	EE 22
Elbow DN28	EE 28
Elbow DN32	EE 32
Elbow DN40	EE 40

MALE ELBOWS



Description	Code
DN22 x 3/4" Male BSP Elbow	EM 22-34

FEMALE ELBOWS



Description	Code
DN15 x 1/2" Female BSP Elbow	EF 15-12
DN15 x 3/4" Female BSP Elbow	EF 15-34
DN22 x 3/4" Female BSP Elbow	EF 22-34
DN22 x 1" Female BSP Elbow	EF 22-10
DN28 x 1 1/4" Female BSP Elbow	EF 28-114
DN32 x 1 1/2" Female BSP Elbow	EF 32-112
DN40 x 2" Female BSP	EF 40-20

WINGED FEMALE ELBOWS



Description	Code
DN15 x 1/2" Female BSP	EFW 15-12
DN15 x 3/4" Female BSP	EFW 15-34

EQUAL TEES



Description	Code
DN15 Equal Tee	TT 15
DN22 Equal Tee	TT 22
DN28 Equal Tee	TT 28
DN32 Equal Tee	TT 32
DN40 Equal Tee	TT 40

FEMALE TEES**Description**

DN15 x 1/2" Female Adapter Tee
 DN22 x 3/4" Female Adapter Tee

Code

TF 15-12
 TF 22-34

REDUCING TEES**Description**

DN22 x DN15 x DN15 Reducing Tee
 DN22 x DN22 x DN15 Reducing Tee
 DN22 x DN15 x DN22 Reducing Tee
 DN28 x DN28 x DN22 Reducing Tee
 DN28 x DN28 x DN15 Reducing Tee
 DN32 x DN32 x DN28 Reducing Tee
 DN32 x DN32 x DN22 Reducing Tee
 DN40 x DN40 x DN32 Reducing Tee
 DN40 x DN40 x DN28 Reducing Tee

Code

TR 22-15-15
 TR 22-22-15
 TR 22-15-22
 TR 28-28-22
 TR 28-28-15
 TR 32-32-28
 TR 32-32-22
 TR 40-40-32
 TR 40-40-28

**COPPER / FLEXIGAS TEE - TYPE 1
(FLEXIGAS FEED + 2 X COPPER)****Description**

Flexigas DN15 x Copper 15 x Copper 15
 Flexigas DN15 x Copper 15 x Copper 22
 Flexigas DN15 x Copper 22 x Copper 15
 Flexigas DN15 x Copper 22 x Copper 22
 Flexigas DN15 x Copper 22 x Copper 28
 Flexigas DN22 x Copper 15 x Copper 28
 Flexigas DN22 x Copper 22 x Copper 22
 Flexigas DN22 x Copper 22 x Copper 28
 Flexigas DN22 x Copper 28 x Copper 15
 Flexigas DN22 x Copper 28 x Copper 22
 Flexigas DN22 x Copper 28 x Copper 28
 Flexigas DN28 x Copper 35 x Copper 15
 Flexigas DN28 x Copper 35 x Copper 22
 Flexigas DN28 x Copper 35 x Copper 28
 Flexigas DN28 x Copper 35 x Copper 35
 Flexigas DN32 x Copper 42 x Copper 15
 Flexigas DN32 x Copper 42 x Copper 22
 Flexigas DN32 x Copper 42 x Copper 28
 Flexigas DN32 x Copper 42 x Copper 35
 Flexigas DN32 x Copper 42 x Copper 42
 Flexigas DN40 x Copper 54 x Copper 15
 Flexigas DN40 x Copper 54 x Copper 22
 Flexigas DN40 x Copper 54 x Copper 28
 Flexigas DN40 x Copper 54 x Copper 35
 Flexigas DN40 x Copper 54 x Copper 42
 Flexigas DN40 x Copper 54 x Copper 54

Code

FG15-CC15-CC15
 FG15-CC15-CC22
 FG15-CC22-CC15
 FG15-CC22-CC22
 FG15-CC22-CC28
 FG22-CC15-CC28
 FG22-CC22-CC22
 FG22-CC22-CC28
 FG22-CC28-CC15
 FG22-CC28-CC22
 FG22-CC28-CC28
 FG28-CC35-CC15
 FG28-CC35-CC22
 FG28-CC35-CC28
 FG28-CC35-CC35
 FG32-CC42-CC15
 FG32-CC42-CC22
 FG32-CC42-CC28
 FG32-CC42-CC35
 FG32-CC42-CC42
 FG40-CC54-CC15
 FG40-CC54-CC22
 FG40-CC54-CC28
 FG40-CC54-CC35
 FG40-CC54-CC42
 FG40-CC54-CC54

Flexigas™ Products

COPPER / FLEXIGAS TEE - TYPE 2 (COPPER FEED + 2 X FLEXIGAS)



Description

Code

Copper 22 x FG DN15 x FG DN15	CC22-FG15-FG15
Copper 22 x FG DN15 x FG DN22	CC22-FG15-FG22
Copper 28 x FG DN15 x FG DN15	CC28-FG15-FG15
Copper 28 x FG DN15 x FG DN22	CC28-FG15-FG22
Copper 28 x FG DN22 x FG DN15	CC28-FG22-FG15
Copper 28 x FG DN22 x FG DN22	CC28-FG22-FG22
Copper 35 x FG DN28 x FG DN15	CC35-FG28-FG15
Copper 35 x FG DN28 x FG DN22	CC35-FG28-FG22
Copper 35 x FG DN28 x FG DN28	CC35-FG28-FG28
Copper 42 x FG DN32 x FG DN15	CC42-FG32-FG15
Copper 42 x FG DN32 x FG DN22	CC42-FG32-FG22
Copper 42 x FG DN32 x FG DN28	CC42-FG32-FG28
Copper 42 x FG DN32 x FG DN32	CC42-FG32-FG32
Copper 54 x FG DN40 x FG DN15	CC54-FG40-FG15
Copper 54 x FG DN40 x FG DN22	CC54-FG40-FG22
Copper 54 x FG DN40 x FG DN28	CC54-FG40-FG28
Copper 54 x FG DN40 x FG DN32	CC54-FG40-FG32
Copper 54 x FG DN40 x FG DN40	CC54-FG40-FG40

COPPER / FLEXIGAS TEE - TYPE 3 (FLEXIGAS FEED / END, COPPER MIDDLE BRANCH)



Description

Code

FG DN15 x FG DN15 x Copper 15	FG15-FG15-CC15
FG DN15 x FG DN15 x Copper 22	FG15-FG15-CC22
FG DN15 x FG DN15 x Copper 28	FG15-FG15-CC28
FG DN22 x FG DN15 x Copper 22	FG22-FG15-CC22
FG DN22 x FG DN15 x Copper 28	FG22-FG15-CC28
FG DN22 x FG DN22 x Copper 15	FG22-FG22-CC15
FG DN22 x FG DN22 x Copper 22	FG22-FG22-CC22
FG DN22 x FG DN22 x Copper 28	FG22-FG22-CC28
FG DN28 x FG DN28 x Copper 15	FG28-FG28-CC15
FG DN28 x FG DN28 x Copper 22	FG28-FG28-CC22
FG DN28 x FG DN28 x Copper 28	FG28-FG28-CC28
FG DN28 x FG DN28 x Copper 35	FG28-FG28-CC35
FG DN32 x FG DN32 x Copper 15	FG32-FG32-CC15
FG DN32 x FG DN32 x Copper 22	FG32-FG32-CC22
FG DN32 x FG DN32 x Copper 28	FG32-FG32-CC28
FG DN32 x FG DN32 x Copper 35	FG32-FG32-CC35
FG DN32 x FG DN32 x Copper 42	FG32-FG32-CC42
FG DN40 x FG DN40 x Copper 15	FG40-FG40-CC15
FG DN40 x FG DN40 x Copper 22	FG40-FG40-CC22
FG DN40 x FG DN40 x Copper 28	FG40-FG40-CC28
FG DN40 x FG DN40 x Copper 35	FG40-FG40-CC35
FG DN40 x FG DN40 x Copper 42	FG40-FG40-CC42
FG DN40 x FG DN40 x Copper 54	FG40-FG40-CC54

**COPPER / FLEXIGAS TEE - TYPE 4
(COPPER FEED / END, FLEXIGAS
MIDDLE BRANCH)**



Description

Code

Copper 22 x Copper 22 x FG DN15	CC22-CC22-FG15
Copper 28 x Copper 28 x FG DN22	CC28-CC28-FG22
Copper 35 x Copper 35 x FG DN28	CC35-CC35-FG28
Copper 42 x Copper 42 x FG DN32	CC42-CC42-FG32
Copper 54 x Copper 54 x FG DN42	CC54-CC54-FG42
Copper 28 x Copper 28 x FG DN15	CC28-CC28-FG15
Copper 35 x Copper 35 x FG DN15	CC35-CC35-FG15
Copper 35 x Copper 35 x FG DN22	CC35-CC35-FG22
Copper 42 x Copper 42 x FG DN15	CC42-CC42-FG15
Copper 42 x Copper 42 x FG DN22	CC42-CC42-FG22
Copper 42 x Copper 42 x FG DN28	CC42-CC42-FG28
Copper 54 x Copper 54 x FG DN15	CC54-CC54-FG15
Copper 54 x Copper 54 x FG DN22	CC54-CC54-FG22
Copper 54 x Copper 54 x FG DN28	CC54-CC54-FG28
Copper 54 x Copper 54 x FG DN32	CC54-CC54-FG32
Copper 22 x Copper 15 x FG DN15	CC22-CC15-FG15
Copper 28 x Copper 15 x FG DN22	CC28-CC15-FG22
Copper 28 x Copper 22 x FG DN22	CC28-CC22-FG22
Copper 22 x Copper 22 x FG DN22	CC22-CC22-FG22

EXTRA SILICONE TAPE



Description

Code

2m x 25mm Silicone Tape	STP-01
11m x 25mm Silicone Tape	STP-02

**Flexigas include 1x roll of 2m tape FREE in every box and spool*

CSST CUTTERS



Description

Code

CSST Tubing Cutter DN15-32	TC-01
CSST Tubing Cutter DN32-50	TC-02

FG WRAP™

Optional Patent Pending replacement for silicone tape

Code

WRAP-15

WRAP-22

WRAP-28

WRAP-32



Flexigas

+65 6746 9933

SWEE HUAT HENG ENGINEERING PTE LTD
1 Loyang Way 1 Singapore 508702
enquiry@shhe.com.sg
or visit www.shhe.com.sg